

JS SMART C+

VANE-WHEEL SINGLE-JET DRY WATER METERS (DN15-20)

APPLICATION

For measuring the flow and volume of water with a temperature up to 30°C or 50°C, or warm water with a temperature up to 90°C in the closed-circuit system with the full flow of the flux, and on the maximum working pressure up to 16 bar (PN16). Suitable for installation in the horizontal hoses (pipelines) with the counter directed upwards (**H**) and in vertical or horizontal hoses with the counter directed sideways (**V**). Water meters SMART C+ in standard version are equipped with low eight-barrel counter (IP65), antimagnetic protection SN +, brass housing and they are adapted to operation in the systems of remote data transfer (AMR).



JS SMART C+

METROLOGICAL CLASS (MID):

- Cold water R160 - H; R63 - V,
- Warm water R160 - H; R63 - V,

Table 1. BASIC TECHNICAL DATA

Type	Q ₃ [m ³ /h]	DN [mm]	Length [mm]	Connection	Weight [kg]	
WATER METERS for cold water						
JS 1,6-02 Smart C+	R160	1,6	15	110	G $\frac{3}{4}$	0,43
JS 2,5-02 Smart C+	R160	2,5	15	110**	G $\frac{3}{4}$	0,43
JS 2,5-G1-02 Smart C+	R160	2,5	20	130	G1	0,57
JS 4-02 Smart C+	R160	4	20	130	G1	0,53
WATER METERS for warm water*						
JS90 1,6-02 Smart C+	R160	1,6	15	110	G $\frac{3}{4}$	0,43
JS90 2,5-02 Smart C+	R160	2,5	15	110**	G $\frac{3}{4}$	0,43
JS90 2,5-G1-02 Smart C+	R160	2,5	20	130	G1	0,57
JS90 4-02 Smart C+	R160	4	20	130	G1	0,53

Counter version IP68 on request

*) Special design of water meters available on request:

-02-S – with hard bearings (water meters for warm water circulation systems)

***) The length of 115 or 80 mm available on request (for JS 2,5 and JS90 2,5 – brass housing)

PRODUCT FEATURES

- Resistant to strong external magnetic field
- Preequipped for installation of: radio module for communication in the Wireless M-Bus, impulse module and M-Bus module
- Readings reliability – fulfils the newest metrological requirements of MID
- Easy reading of the water meter counter
- Hermetic counter (with increased tightness) resistant to steaming
- Counter mechanism with blockade against multiple rotating, at rotation angle more than 360°
- Protection against mechanical tampering
- Protection limiting the results of water freezing
- Double-sided rotor bearing
- Outlet port of water meter housing suitable for optional installation of a return valve